

iGXC11T Performance Curve

Max Heating Capacity(kW)												
Ambient temp./°C Outlet temp./°C	-25	-20	-15	-10	-7	0	2	7	15	25	35	43
35	7.47	9.04	10.24	11.03	11.38	11.43	11.48	13.92	16.82	17.41	17.49	19.06
45	7.04	8.70	9.78	10.23	11.14	11.16	11.20	13.04	16.05	16.61	16.37	18.08
55	6.54	7.75	9.48	10.04	10.58	10.63	10.70	12.37	15.24	15.26	15.14	17.56
65	5.46	7.06	9.06	9.47	9.89	10.08	10.23	11.50	12.37	14.23	14.04	16.05
70	/	6.54	8.17	8.46	8.99	9.04	9.25	10.71	11.32	11.03	/	/
75	/	/	/	7.27	8.35	8.46	8.68	9.69	10.16	/	/	/

COP(W/W)												
Ambient temp./°C Outlet temp./°C	-25	-20	-15	-10	-7	0	2	7	15	25	35	43
35	2.32	2.57	2.94	3.06	3.23	3.70	3.89	4.16	4.98	6.05	7.02	7.69
45	1.98	2.08	2.66	2.78	2.91	3.18	3.32	3.56	4.10	4.72	5.78	6.15
55	1.68	1.83	2.42	2.57	2.74	2.56	2.68	2.88	3.23	4.08	4.27	4.99
65	1.26	1.53	1.91	2.02	2.13	2.27	2.37	2.37	2.56	2.68	3.14	3.70
70	/	1.31	1.78	1.79	1.91	1.93	1.97	1.95	2.06	2.80	/	/
75	/	/	/	1.55	1.64	1.71	1.74	1.43	1.66	/	/	/

